

NO. 9 SOLVENT

Revision 1 . January 28, 2010

Page 1 of 8

## SECTION 1 ● PRODUCT AND COMPANY IDENTIFICATION

Product Numbers 902, 902CN, 904, 904CN, 904B, 904P, 916, 916CN, 932, 9501

Product Name Hoppe's #9 Solvent

Synonyms None

Products Uses Removes powder, lead, metal fouling and rust from guns

Revision Number

Revision Date January 28, 2010
Print Date January 28, 2010

24 hr Emergency Phone Number

800-255-3924

(CHEM-TEL)

MANUF	ACTURER INFORMATION	DISTR	RIBUTOR INFORMATION
Company Name	Tri-Pac Inc.	Company Name	Bushnell Outdoor Products
Address	17336 M-60 East	Address	9200 Cody
	Vandalia, MI 49095		Overland Park, KS 66214
Phone Number	269-476-2303	Phone Number	800-423-3537
Fax Number	269-476-2302	Fax Number	913-752-3570

## **SECTION 2 ● HAZARDS IDENTIFICATION**

EMERGENCY OVERVIEW

DANGER! CONTENTS EXTREMELY FLAMMABLE. VAPOR MAY FORM AN EXPLOSIVE MIXTURE WITH AIR. VAPOR CAN TRAVEL TO A SOURCE OF IGNITION AND FLASH BACK. AVOID CONTACT WITH SKIN AND EYES. VAPOR HARMFUL. EYE AND SKIN IRRITANT. HARMFUL OR FATAL IF SWALLOWED. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

OSHA Classification This product is a "hazardous chemical" as defined by the OSHA Hazard Communication Standard, 29

CFR 1910.1200.

European Classification F, Xn, Xi

R 11-36/37/38-65-66

S 2-7-16-23-24/25-26-36/37/39-45-61-62

WHMIS Classification B2, D2B, E





	HEALTH I	HAZARDS	PHYSICAL HAZARDS					
Irritant	1	Sensitizer	Combustible	Explosive		Pyrophoric		
Toxic		Highly Toxic	Flammable	Oxidizer		Water Reactive		
Corrosive		Carcinogenic	Compressed Gas	Organic Peroxide		Unstable		

	LABELING REQUIREMENTS										
CANADA	UNITED STATES	EUROPE & AUSTRALIA	GHS								
	DANGER CONTENTS EXTREMELY FLAMMABLE EYE AND SKIN IRRITANT	<b>8</b> ×	♦ ♦								



NO. 9 SOLVENT

Revision 1 & January 28, 2010

Page 2 of 8

#### POTENTIAL HEALTH EFFECTS AND SIGNS / SYMPTOMS OF EXPOSURE

Eye Contact Liquid contact may cause pain along with moderate eye irritation.

Skin Contact Prolonged or repeated exposure may cause skin irritation. Repeated contact may cause drying flaking

of skin. May cause more severe response if confined to skin.

Ingestion May cause irritation to membranes of the mouth, throat, and gastrointestinal tract resulting in vomiting

and/or cramps. Aspiration of vom it into the lungs may cause inflammation, and possible chemical

pneumonitis, bronchopneumonia, or pulmonary edema.

Inhalation Prolonged or repeated overexposure is anesthetic. May cause irritation of the respiratory tract, or acute

nervous system depression characterized by headache, dizziness, staggering gait, confusion or death.

Irritation of the mucous membranes, coughing, and dyspnea are also possible.

Effects of Chronic Exposure Reports have associated repeated and piolonged occupational overexposure to solvents with irreversible

brain and ner vous system damage (sometimes referr ed to as "Solvent or Painter" s Syndrome").

Intentional misuse by concentrating and inhaling this product may be harmful or fatal.

Medical Conditions Aggravated

May aggravate personnel with pre-existing disorders associated with any of the Target Organs.

Types of Hazards Sensory Irritation

Target Organs Eyes, Skin, Respiratory System, Central Nervous System, Liver, Blood

Routes of Exposure Skin contact, skin absorption, eye contact, inhalation

Potential Environmental Effects See Section 12 for environmental effects

## SECTION 3 ● COMPOSITION / INFORMATION ON INGREDIENTS

ID	INGREDIENT	CAS NUMBER	EINECS	EU CLASSIFICATION	% WT
1	Kerosene	008008-20-6	232-366-4	Xn; 65	15 - 40
2	Ethyl Alcohol	000064-17-5	200-578-6	F; 11	15 - 40
3	Oleic Acid	000112-80-1	204-007-1	_	_
4	Amyl Acetate	000628-63-7	211-047-3	10-65	5 - 10
5	Ammonium Hydroxide	001336-21-6	215-647-6	N, C; 34-50	1 - 5

Risk Phrases See Section 15 for risk phrase text

LD50 and LC50 Information See Section 11 for toxicological information

Occupational Exposure Limits See Section 8 for OELs

#### SECTION 4 ● FIRST AID MEASURES

Ingestion DO NOT INDUCE VOMITING! ASPIRATION HAZARD. This material may enter the lungs during

vomiting. Immediately have the victim drink plenty of water. Keep airways free. Contact a physician immediately. Never give anything by mouth if victim is rapidly losing consciousness, unconscious, or

convulsing.

Skin Contact Remove with soap and water, rinsing and repeating for 15 minutes. Use ski n cream to counter any

resulting dryness. Consult a physician if irritation continues. If large skin area is affected, remove

contaminated clothing.

Eye Contact Immediately flush with clear water for at least 15minutes, including under the eyelids. Consult a doctor.

Remove to fresh air. If not breathinggive artificial respiration. If breathing is difficult give oxygen. Seek

medical attention if symptoms persist or if unconscious.

Notes to Physician Treat symptomatically.

Antidotes No specific antidote.

Inhalation

#### SECTION 5 ● FIRE FIGHTING MEASURES

Flash Point  $> 55 \,^{\circ}F \, (12.8 \,^{\circ}C)$ Autoignition Temperature  $410 \,^{\circ}F \, (210.0 \,^{\circ}C)$ 



NO. 9 SOLVENT

Revision 1 & January 28, 2010

Page 3 of 8

Explosive Limits 0.70% to 19.00%

Conditions of Flammability Heat, sparks, flame, red hot metal

Extinguishing Media Water, CO2, dry chemical, or universal aqueous film forming foam

Unsuitable Extinguishing Media Water jet

Hazardous Combustion Products Oxides of carbon (CO, CO2), smoke, and vapors
Sensitivity to Mechanical Impact Probably not sensitive as material is stable.

Sensitivity to Static Discharge Vapor within the flammable limits may be ignited by a static discharge of sufficient energy.

pressure. Firemen should wear self-contained breathing apparatus.

Special Explosion Hazards FLAMMABLE LIQUID. Vapors can form a n explosive mixture with air and can travel to a source of

ignition (spark or flame) and flash back.

Autoreactivity / Oxidizing Properties Not available

#### SECTION 6 ● ACCIDENTAL RELEASE MEASURES

Environmental Precautions Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent.

Containment Procedures Released content may be contained with oil/solvent absorbent pads, booms, and/or absorbents.

Cleanup Procedures Avoid breathing vapors and ventilate area well. Rem ove sources of ignit ion and use non-sparking

equipment. Soak up material with inert absorbent and place in safety containers for proper disposal.

Other Information Consult the North American Emergency Response Gudebook or similar resources providing emergency

response information for dealing with accidents, spills, leaks, and/or fires involving dangerous goods.

Prohibited Materials Combustible absorbent material such as sawdust, use of equipment that may cause sparking.

Reporting Requirements Report releases that reach surface water or groundwater in any amount. Spills, leaks, andoverfills from

a regulated underground storage tank should also be reported. Repotable quantities for spills onto the ground depend on site conditions, such as the type of soil and the type of material spilled, and Federal

and local agencies often have different reportable quantities.

#### **SECTION 7 ● HANDLING AND STORAGE**

Precautions for Safe Handling / Use KEEP OUT OF THE REACH OF CHILDREN.

Storage Requirements / Conditions For storage of all flammable materials, conform to NFPA 30 Flammable and Combustible Liquid. Keep

containers tightly closed and stored in a well-ventilated place. Keep away from sources of ignition.

Special Packaging Materials Not applicable.

### SECTION 8 ● EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational Exposure Limits

ID	UNITED STATES OSHA PEL	UNITED STATES NIOSH REL	UNITED STATES NIOSH IDLH	UNITED STATES ACGIH TLV	AUSTRALIA TWA	GERMANY MAK	JAPAN OEL
1	None Established	100 mg/m3	None Established	200 mg/m3	None Established	None Established	None Established
2	1000 ppm	None Established	None Established	1000 ppm	1000 ppm	500 ppm	None Established
3	None Established	None Established	None Established	None Established	None Established	None Established	None Established
4	100 ppm	100 ppm	1000 ppm	50 ppm	50 ppm	50 ppm	100 ppm
5	None Established	None Established	None Established	None Established	None Established	None Established	None Established

ID	CANADA ALBERTA OEL	CANADA BC TWA	CANADA ONTARIO TWAEV	CANADA QUEBEC TWA	MEXICO MPEL-PTA	UNITED KINGDOM WEL	UNITED STATES AIHA WEEL
1	None Established	200 mg/m3	200 mg/m3	None Established	None Established	None Established	None Established
2	1000 ppm	1000 ppm	1000 ppm	1000 ppm	1000 ppm	1000 ppm	None Established
3	None Established	None Established	None Established	None Established	None Established	None Established	None Established
4	100 ppm	50 ppm	50 ppm	100 ppm	100 ppm	None Established	None Established
5	None Established	None Established	None Established	None Established	None Established	None Established	None Established



NO. 9 SOLVENT

Page 4 of 8

Revision 1 & January 28, 2010

Use with adequate ventilation. General ventilation (typically 10 air changes per hour) should be used. **Engineering Measures** 

Rates should be matched to conditions. Local exhaust ventilation or an enclosed handling system may

be necessary to control air contamination below that of the lowest OEL from the table above.

**Biological Exposure Indices** None Established

Avoid breathing vapors and contact with the skin and eyes. Always replace overcap when not in use. **General Hygiene Considerations** 

Keep out the reach of children. Wash hands after use.

Thermal Hazards This product does not present a thermal hazard.

#### PERSONAL PROTECTIVE EQUIPMENT





**Respiratory Protection** An approved respirator with an organic vaporcartridge may be permissible undercertain circumstances where airborne concentrations are expected to exceed occupational exposure limits. If respirators are

needed, in the United States compliance with OSHA standard 29 CFR 1910.134 is necessary.

**Skin Protection** For brief contact, no precauti ons other than clean body-cove ring clothing should be needed. When prolonged or repeated contact could occur, use protective clothing impervious to the ingredients listed.

**Eye/Face Protection** Safety glasses with side shields are recommended as a minimum for any type of chemical handling. Other Protective Equipment

Safety showers and eye-wash stations should be available in the near where the material will be used.

### SECTION 9 ● PHYSICAL AND CHEMICAL PROPERTIES

**Boiling Point** > 177 °F (47.0 °C) > -173 °F (-114.2 °C) Melting / Freezing Point 410 °F (210.0 °C) Flash Point > 55 °F (12.8 °C) Autoignition Temperature, Liquid **Explosive Limits** 0.70% to 19.00% **Decomposition Temperature** Not Available Flammability Class IB Flammable Liquid Density (H<sub>2</sub>O = 1)0.844 g/cc 7.031 lbs/gal Molecular Weight Not Available Weight Vapor Pressure Not Available Not Available pН Vapor Density 9.70 g/cc Maximum Evaporation Rate (BuAC = 1) Not Available **Physical State** Liquid **Partition Coefficient** Not Available Viscosity Not Available Refractive Index Not Available Odor Threshold Not Available **Heat of Combustion** Not Available Distinct Water Solubility Not Available

Appearance / Color Clear light to dark amber

**VOC Content** Percent Volatile 73% Wt (75% Vol) Max 4.910 lbs/gal (588.331 g/L)

Percent VOC 71% Wt (74% Vol) Max **HAP Content** None

Solids Content None **Maximum Incremental Reactivity** 1.145 g O<sub>3</sub>/g

### **SECTION 10 ● STABILITY AND REACTIVITY**

Stability Stable **Physical Hazards** Flammable **Conditions to Avoid** Not Available

**Hazard Polymerization** Not expected to occur

Material Incompatibility Strong oxidizing agents, ammonia, hydrogen peroxide, strong reducing agents, potassium tert-butoxide,

bases, acids, perchloric and permonosulfuric acids, alkali metals, halogens, dimethyl sulfate



NO. 9 SOLVENT

Page 5 of 8

Revision 1 \* January 28, 2010

Conditions of Reactivity Heat, sparks, flame, red hot metal

Decomposition Products Oxides of carbon

## **SECTION 11 ● TOXICOLOGICAL INFORMATION**

Irritancy of Product The following ingredients are eye irritants: Ethyl Alcohol. The following ingredients are skin irritants:

Kerosene, Ammonium Hydroxide.

Sensitization to Product

None of the ingredients and considered known or suspected sensitizers.

Carcinogen Data

None of the ingredients are considered known or suspected carcinogens.

Reproductive Toxicity

None of the ingredients are considered known or suspected reproductive toxicants.

Teratogenicity

None of the ingredients are considered known or suspected teratogens.

Mutagenicity

The following ingredients are considered mutagens: Ethyl Alcohol

Synergistic Products No known synergistic properties.

LD<sub>50</sub> and LC<sub>50</sub> Information

	LD50 a	Do and Low information										
ı	ō	ORAL LD50	DERMAL LD50	INHALATION LC50								
	1	> 5000 mg/kg, rat	> 2000 mg/kg, rabbit	> 5.28 mg/L /4hr, rat								
ı	2	6200 mg/kg, rat	> 20000 mg/kg, rabbit	> 8000 mg/L /4hr, rat								
	3	58000 mg/kg, rat	Not Available	Not Available								
ı	4	6500 mg/kg, rat	Not Available	Not Available								
ĺ	5	350 mg/kg. rat	Not Available	1.4 mg/L /4hr. rat								

## SECTION 12 ● ECOLOGICAL INFORMATION

MobilityNot AvailablePersistanceNot AvailableDegradibilityNot AvailableBioaccumulationNot Available

Other Ecologic Data Do not allow to enter waters, waste water, or soil. Harmful to aquatic organisms, may cause long-term

adverse effects in the aquatic environment.

Effects on the Ozone Layer This product does not contain any ozone depleting ingredients.

**Ecotoxicity** 

ID	FISH	INVERTEBRATES	AQUATIC PLANTS	MICROORGANISMS
1	Not Available	Not Available	Not Available	Not Available
2	LC50: 11000 mg/L /96 hr	EC50: 10800 mg/L /24 hr	NOEC: 5000 mg/L /7 day	NOEC: 5600 mg/L /16 hr
3	LC50: 205 mg/L /96 hr	Not Available	Not Available	Not Available
4	LC50: 65 mg/L /96 hr	Not Available	Not Available	Not Available
5	Not Available	Not Available	Not Available	Not Available

### **SECTION 13 ● DISPOSAL CONSIDERATIONS**

Waste Disposal Product is suitable for burning in an enclosed, controlled burner for fuel value. Hazard characteristics

and regulatory waste stream classification can change with product use and location. Accordingly, it is the responsibility of the userto determine the proper storage, transportation, treatment, and/or disposal methodologies for spent materials and residues at the time of disposition. All waste material must be disposed of in compliance with the respective national, federal, state, and/or local regulations.

Waste Disposal of Packaging

Consult with your local landfill to determine if empty small containers can be disposed of regular trash pickup. For disposal of large containers (typically 10 gallon or larger), or for containers not suitable for

landfill, a licensed reconditioner should be used.

Landfill Precautions Not Available
Incineration Precautions Not Available



NO. 9 SOLVENT

Revision 1 & January 28, 2010

Page 6 of 8

## **SECTION 14 ● TRANSPORTATION INFORMATION**

THE FOLLOWING APPLIES TO PRODUCT NUMBERS 902, 902Z, 904, 904B, 904P, 916:

#### **DOT SHIPPING INFORMATION (United States)**

ORM-D

PROPER SHIPPING NAME: ... Consumer Commodity HAZARD CLASS: .... ORM-D

PACKING GROUP: UN or ID NUMBER: NAERG GUIDE NUMBER: 171

### ICAO/IATA SHIPPING INFORMATION (International Air)



PROPER SHIPPING NAME: . . Flammable Liquid NOS (Kerosene, Ethanol, Amyl Acetate Mixture), Limited Quantity

| HAZARD CLASS: 3 | PACKAGING GROUP: || | UN or ID NUMBER: UN 1993

#### **IMDG SHIPPING INFORMATION (International Ocean)**



PROPER SHIPPING NAME: . . . Flammable Liquid NOS (Kerosene, Ethanol, Amyl Acetate Mixture), Limited Quantity

 CLASS:
 3

 PACKAGING GROUP:
 II

 SUBSIDIARY RISK(S):

 UN or ID NUMBER:
 UN 1993

 PACKING INSTRUCTIONS:
 P001

 EmS NO.:
 F-E, S-E

 STOWAGE:
 Category B

#### **ADR SHIPPING INFORMATION (European Union)**



PROPER SHIPPING NAME: . . . Flammable Liquid NOS (Kerosene, Ethanol, Amyl Acetate Mixture), Limited Quantity

 ADR CLASS:
 3

 PACKAGING GROUP:

 UN or ID NUMBER:
 UN 1993

 CLASSIFICATION CODE:
 F1

 HAZARD IDENTIFICATION NO:
 33

 EMERGENCY ACTION CODE:
 •3YE

#### TDG SHIPPING INFORMATION (Canada)



PROPER SHIPPING NAME: . . . Flammable Liquid NOS

(Kerosene, Ethanol, Amyl Acetate Mixture), Limited Quantity

 HAZARD CLASS:
 3

 PACKAGING GROUP:
 II

 UN or ID NUMBER:
 UN 1993

#### NMFC DESCRIPTION (United States)

ITEM DESCRIPTION: Compounds Cleaning ITEM NUMBER: 48580 Sub 3

CLASS: 48580 Su.

#### THE FOLLOWING APPLIES TO PRODUCT NUMBERS 932, 9501:

#### **DOT SHIPPING INFORMATION (United States)**



PROPER SHIPPING NAME: ... Flammable Liquid NOS

(Kerosene, Ethanol, Amyl Acetate Mixture)

 HAZARD CLASS:
 3

 PACKING GROUP:
 //

 UN or ID NUMBER:
 UN 1993

 NAERG GUIDE NUMBER:
 171

#### ICAO/IATA SHIPPING INFORMATION (International Air)



PROPER SHIPPING NAME: . . Flammable Liquid NOS (Kerosene, Ethanol, Amyl Acetate Mixture)

 HAZARD CLASS:
 3

 PACKAGING GROUP:
 //

 UN or ID NUMBER:
 UN 1993

#### **IMDG SHIPPING INFORMATION (International Ocean)**



PROPER SHIPPING NAME: . . . Flammable Liquid NOS (Kerosene, Ethanol, Amyl Acetate Mixture)

 SUBSIDIARY RISK(S):

 UN or ID NUMBER:
 UN 1993

 PACKING INSTRUCTIONS:
 P001

 EmS NO.:
 F-E, S-E

 Ems NO.:
 F-E, S-E

 STOWAGE:
 Category B

 MFAG NO.:
 310, 313

### **ADR SHIPPING INFORMATION (European Union)**



PROPER SHIPPING NAME: . . . Flammable Liquid NOS (Kerosene, Ethanol, Amyl Acetate Mixture)

 ADR CLASS:
 3

 PACKAGING GROUP:

 UN or ID NUMBER:
 UN 1993

 CLASSIFICATION CODE:
 F1

 HAZARD IDENTIFICATION NO:
 33

 EMERGENCY ACTION CODE:
 03YE

#### TDG SHIPPING INFORMATION (Canada)



PROPER SHIPPING NAME: . . . Flammable Liquid NOS


(Kerosene, Ethanol, Amyl Acetate Mixture)

 HAZARD CLASS:
 3

 PACKAGING GROUP:
 II

 UN or ID NUMBER:
 UN 1993

#### NMFC DESCRIPTION (United States)



CLASS: 55

Special Transport Precautions Not Available



NO. 9 SOLVENT

Revision 1 . January 28, 2010

Page 7 of 8

## **SECTION 15 ● REGULATORY INFORMATION**

#### United States - Federal

	TSCA	SARA 302						CLEAN	CLEAN			
ID	INVENTORY	EHS	RCRA	CERCLA	SARA 313	FIRE	REACTIVITY	ACUTE	CHRONIC	PRESSURE	AIR ACT	WATER ACT
1	/	_	_	_	_	/	_	/	/	_	_	_
2	/	_	_		_	/	_	/	/	_	_	_
3	/	_	_	_	_	_	_	_	_	_	_	
4	/	_	_	5000#	_	_	_	_	_	_	_	5000#
5	/	_	_	1000#	_	_	_	/	/	_	_	_

#### **United States - States**

ID	CALIFORNIA	DELAWARE	FLORIDA	MASSACHUSETTS	PENNSYLVANIA	MINNESOTA	NEW JERSEY	NEW YORK	WASHINGTON	
1	_	_	/	5	_	_	_	_	_	
2	_	_	/	2,4,5,6 *T1*	_	AO	_		/	
3	_	_	_	_	_	_	_	_		
4	_	/	/	2,4,5,6 F8	E	AO	_	/	/	
5	_	/	_	F8	E	_	/	/		

#### Canada

		WHMIS CATEGORIES										AL LISTS	
ID	Α	В	С	D1A	D1B	D2A	D2B	D3	E	DSL	NDSL	NPRI	CWC
1	В3	_	_	_	_	/	_	_	_	/	_	_	_
2	B2	_	_	_	<u>—</u>	/	_	_	_	/	_	5	_
3	_	_	_	_	_	_	_	_	_	/	_	_	_
4	B2	_	_	_		_	_	_	_	/	_	_	_
5	_	_	_	_	_	_	_	_	/	/	_	_	_

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

**European Union** 

CODE	RISK PHRASES
R 11	Highly Flammable
R 50/52	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R 65	Harmful: may cause lung damage if swallowed
R 66	Repeated exposure may cause skin dryness or cracking

CODE	SAFETY PHRASES
S 2	Keep out of the reach of children
S 7	Keep container tightly closed
S 23	Do not breath fumes
S 24/25	Avoid contact with skin and eyes
S 26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
S 36/37/39	Wear suitable protective clothing, gloves and eye/face protection
S 45	In case of accident or you feel unwell, seek medical advice immediately
S 61	Avoid release to the environment
S 62	If swallowed do not induce vomiting; seek medical advise immediately

**RoHS Compliance** 



This product is RoHS compliant according to the definitions and restrictions given by Directive 2002/95/EC and The Council of January 27, 2003 on the restriction of the use of certain hazardous substances in electrical and electronic equipment.

Australia

Poisons Schedule Number

None of the ingredients are present at or above a concentration necessary for allocation of a Poisons Schedule Number.

Chemical Inventory Status All of the ingredients are listed on the Australian Inventory of Chemical Substances(AICS) or are exempt.



**NO. 9 SOLVENT** 

Revision 1 . January 28, 2010

Page 8 of 8

## **SECTION 16 ● OTHER INFORMATION**

Disclaimer of Liability

The information contained herein is based upon data provided to us by our suppliers, and reflects our best judgement. However, no warranty of merchantability, fitness for any use, or any other warranty or guarantee is expressed or implied egarding the accuracy of such data, or the results to be obtained from use thereof. Since theinformation contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, we do not a ssume any responsibility for the results of such application. This information is furnished upon the condition hat the persons receiving it shall make their own determinations of the suitability of the material for any particular use. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist.

Revision History
MSDS Prepared By

Revision 1, 01/28/2010, Original

Hazard Communication Associates, msds@hazcom411.com